

**ARDON®**

TECHNICAL DATA SHEET

WINFINE WP

HANDLING IN DRY AND WET ENVIRONMENTS WITH PROTECTION AGAINST VERY LOW AND HIGH TEMPERATURES WITH HIGH MECHANICAL PROTECTION

GERENAL DATA:**Code:** A9144**Material:**

Liner 7G acrylic (inner) + 13G polyester (outer)
 Coating latex (whole) + latex foam with sand pattern (palm)
 Thickness 4,5 mm (in palm)

Description: winter gloves with double knit dipped in latex and latex foam with sand pattern (sand-like finish)**Size(s):** 8 / M – 12 / 3XL**Unit:** Pair**Packing:**


Units in carton 60 pairs
 Units in polybag 12 pairs
 Retail packing sales label



Dimmensions:	8	9	10	11	12
carton HxWxD (cm)	58x28x25	58x28x25	58x28x25	58x28x25	58x28x25
carton (cbm)	0,0406	0,0406	0,0406	0,0406	0,0406

Weight:	8	9	10	11	12
carton (kg)	7,900	8,600	9,000	9,300	9,500
unit (g)	131,7	143,3	150,0	155,0	158,3

Size chart (cm)	8	9	10	11	12
total lenght (A)	25,0	26,0	26,5	27,0	28,0
cuff lenght (B)	7,70	7,70	8,40	8,70	8,90
cuff width (C)	7,70	8,00	8,40	8,80	9,00
palm width (D)	10,0	10,5	11,0	11,3	11,5

*tolerance (A) ± 0,5 (cm)**tolerance (B, C, D) ± 0,3 (cm)*

ARDON SAFETY s. r. o.
 Tržní 2902/14, Přeřov I - Město
 Tel.: 581 250 061 www.ardon.cz



ARDON®

STANDARDS:

(EU) 2016/425

EN ISO 21420:2020

EN 388:2016 + A1:2018

Protective gloves – general requirements and test methods

Protective gloves against mechanical risks

Protection levels:

EN 388



MECHANICAL RISKS

	LVL	score	unit
abrasion resistance:	2	500 – 2.000	cycles
cut resistance:	2	2,5 – 5	index
tearing resistance:	2	25 – 50	N
puncture resistance:	2	60 – 100	N
cut resistance acc. to ISO:	B	5 – 10	N

EN 407:2004

Protective gloves against heat or flame

Protection levels:

EN 407



THERMAL RISKS

	LVL	score
resistance to burning:	X	not measured
resistance to contact heat :	2	250°C for 15s
resistance to convectional heat:	X	not measured
resistance to radiant heat:	X	not measured
resistance to small drops of molten metals:	X	not measured
resistance to large drops of molten metals:	X	not measured

EN 511:2006

Protective gloves against cold

Protection levels:

EN 511



COLD RISKS

	LVL	score
resistance to convection cold:	X	not measured
resistance to contact cold:	2	
water permeability:	1	

SPECIAL FEATURES:

- fully dipped

- multifunctional so-called all-round gloves:

- for work in dry environment (for example with water-based bulk mixtures, especially in building / mortar, paints, etc.)
- high protection against cold and heat (composition of two layers of functional materials and a thick layer of latex better insulate against external influences and keep the body warm)

▪ protection against heat up to 150°C*

▪ latex with sand pattern („sand-like finish“) serves as a barrier against liquids and

palm injuries

- ARDON® design: ▪ mandatory information on inner label

▪ reflective manufacturer's logo

▪ each pairs in each size is retail ready packed

* - according to certification up to 250°C for 15 seconds, but we generally do not recommend exposure to temperatures higher than 150°C, during which latex secondary vulcanizes and heats up



	EAN
A9144/08-SPE	8592390141835
A9144/09-SPE	8592390141842
A9144/10-SPE	8592390141859
A9144/11-SPE	8592390010278
A9144/12-SPE	8592390010261

