

TECHNICAL DATA SHEET

G2011

Eye protection

Article NO: E4015

Lens: clear
 Material- lens: polycarbonate
 Material- frame: soft PVC



Goggles with soft PVC frame and 13-mm long black adjustable rubber band. Clear polycarbonate lens 2 mm thick are resistant to medium-energy shocks (up to 120 m/s) at extreme temperatures (-5 °C - +55 °C) and provides maximum protection. Top-quality goggles providing maximum protection and comfort because of indirect aeration system with 4 valves which protect against penetration of the large powder particles and provide protection against liquid drops, molten metal, hot solid substances and splintering of chemicals. It can be used separately or over dioptric glasses.



Adjustable temple length - NO



Adjustable temple angle - NO



Anti-fogging lens - NO



Anti-scratching lens - NO

Clear lens, 1 BT 9 0

Optical class: 1 permanent use
 Mechanical resistance: BT resistant to medium-energy shocks at extreme temperatures
 Suitable use: 9 molten metal and hot solid substances
 Type of the lens: 0 original lens



This personal protective equipment is in conformity with these harmonized European Standards:

EN 166:2001: Personal eye protection. General requirements.

EN 170:2002: Personal eye-protection - Ultraviolet filters - Transmittance requirements and recommended use.

Certified by Notified body no. 2797 (BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands),
Certificate no CE 749754, dated 26th August 2021.

Pieces in carton:	120
Pieces in box:	10
Polybag packing (pieces):	1
Carton weight:	15 kg
Carton size:	0,129 m ³

Store in dry and dark environment away from direct sunlight at temperatures of -5°C to +55°C, relative humidity 90% and out of sources of gasoline vapors and solvents.

It is recommended to clean after each use. Clean at room temperature with a clean cloth, lightly moistened with a concentrated solution of water and detergent. Do not use hot water, fuel, degreasing fluids, organic solvents or abrasive cleaners.
