

## **TECHNICAL DATA SHEET**

G3011

Eye protection

Article NO: E4018

clear Lens: Material - lens: polycarbonate soft PVC Material- frame:



Goggles with soft PVC frame and 13-mm long black adjustable rubber band. Clear polycarbonate lens 1,5 mm thick are resistant to medium-energy shocks (up to 120 m/s) at extreme temperatures (-5°C - +55°C). Top-quality goggles provide maximum protection and comfort because of direct aeration system which protects against fogging and provides protection against liquid drops, molten metal and hot solid substances. It can be used separately or over dioptric glasses.

	Adjustable temple length	-	NO
	Adjustable temple angle	-	NO
	Anti-fogging lens	-	NO
FA-	Anti-scratching lens	-	NO

<u>Clear lens, 1 BT 9 O</u>		
Optical class:	1	permanent use
Mechanical resistance:	ΒТ	resistant to medium-energy shocks at extreme temperatures
Suitable use:	9	molten metal and hot solid substances
Type of the lens:	0	original lens

ARDON SAFETY s. r. o. Tržní 2902/14, Přerov I - Město Tel.: 581 250 061 www.ardon.cz



This personal protective equipment is in conformity with these harmonized European Standards:

EN 166:2001: Personal eye protection. General requirements. EN 170:2002: Personal eye-protection - Ultraviolet filters - Transmittance requirements and recommended use.

Certified by Notified body no. 2797 (BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands), Certificate no CE 749754, dated 26<sup>th</sup> August 2021.

Pieces in carton:	120
Pieces in box:	10
Polybag packing (pieces):	1
Carton weight:	12 kg
Carton size:	0,095 m <sup>3</sup>

Store in dry and dark enviroment away from direct sunlight at temperatures of -5°C to +55°C, relative humidity 90% and out of sources of gasoline vapors and solvents.

It is recommended to clean after each use. Clean at room temperature with a clean cloth, lightly moistened with a concentrated solution of water and detergent. Do not use hot water, fuel, degreasing fluids, organic solvents or abrasive cleaners.