

## TECHNICAL DATA SHEET

## P3 smoke

Eye protection

Article NO: E4264

Lens: smoke

Material- lens: polycarbonate Material- temples: polycarbonate



Extremely lightweight safety glasses with modern sports styling. They have matte colored polycarbonate temples. Wide smoke polycarbonate lens which are made from one piece protect against UV radiation, it is anti-fogging, anti-scratching and resistant to low-energy shocks (up to 45 m/s) at extreme temperatures (-5 °C - +55 °C). They provide maximum of protection and extremely wide field of vision. Slim-shaped nose bridge provides high level of comfort and better compatibility with ARDON® respirators. K&N surface treatment with increased resistance to fogging (N) and scratching (K).

	A
-decamb	

Adjustable temple length - NO



Adjustable temple angle - NO



Anti-fogging lens - YES



Anti-scratching lens - YES

Smoke lens, UV, 5-3.1 1 FT KNO

Type of filter: 5 UV filter Shade number: 3.1 smoke

Optical class: 1 permanent use

Mechanical resistance: FT resistant to low-energy shocks at extreme

temperatures

K&N surface treatment with increased resistance to

fogging (N) and scratching (K).

Type of the lens: O original lens



This personal protective equipment is in conformity with these harmonized European Standards:

EN 166:2001: Personal eye protection. General requirements.

EN 170:2002: Personal eye-protection - Ultraviolet filters - Transmittance requirements and recommended use.

EN 172:2000: Personal eye protection - Sunlight filters for industrial use.

Certified by Notified body no. 2797 (BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands), Certificate no CE 749754, dated 26<sup>th</sup> August 2021.

1066 EP Amsterdam, The Netherlands), Certificate no CE 749754, dated 26" August 2021.

Pieces in carton: 250
Pieces in box: 10
Polybag packing (pieces): 1
Carton weight: 10 kg
Carton size: 0,103 m³

Store in dry and dark environment away from direct sunlight at temperatures of -5°C to +55°C, relative humidity 90% and out of sources of gasoline vapors and solvents. It is recommended to clean after each use. Clean at room temperature with a clean cloth, lightly moistened with a concentrated solution of water and detergent. Do not use hot water, fuel, degreasing fluids, organic solvents or abrasive cleaners.