



ARDON[®]
WORKWEAR
& OUTDOOR

ARDON[®] DOZER S3

SAFETY SHOES



TECHNICAL SHEET



DRY AIR



**WATER
REPELLENT**



NONMETALLIC



ANTIBACTERIAL



REFLECTIVE



ESD



ARDON[®]
WORKWEAR
 & **OUTDOOR**

ARDON[®] DOZER S3

SAFETY SHOES

ARTICLE G3213

MATERIAL

Upper NUBUK- cowhide leather 1.8 - 2 mm thick, hydrophobic / textile
 Lining MESH laminated breathable fabric
 Sole PU/ PU Superline, dvousložkový nástřík

Toe cap fiberglass 522
 Plate kevlar
 Insole ANATOMIC FOAM anatomically shaped EVA foam, supports longitudinal and transverse arches, absorbs shocks in the heel area

SIZE

36-48

pair

UNIT

Units in a carton 10 pairs

Units in a box 1 pair

DIMENSIONS

36-48
 Carton H x W x D 36,5 x 48 x 65,5
 (cm)

Carton (cbm) 0,115

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	-	240	247	253	260	265	273	279	286	293	303	307	318	323	-	-	-
Foot length cm	-	23,0	23,7	24,3	25,0	25,5	26,3	26,9	27,6	28,3	29,3	29,7	30,8	31,3	-	-	-

DESCRIPTION

Safety footwear with an upper made of high-quality NUBUK cowhide leather and fabric, with a hydrophobic finish. For greater comfort, it is equipped with an anatomically shaped, antistatic, antibacterial, ESD insole. Safety is ensured by a fiberglass toe cap and a flexible Kevlar insole against punctures. The lightweight dual-density polyurethane sole meets SRC anti-slip requirements. The model is ESD, ie it protects against electrostatic discharge and can therefore be used in EPA areas.

TECHNICAL SHEET



ARDON[®]
WORKWEAR
 & **OUTDOOR**

NORMS

(EU) 2016/425

EN ISO 20345:2011 Personal protective equipment – Safety footwear

Category S3 SRC ESD

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WR - upper resistant to water	✓	
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heatup to 300 °C		
HI-insulation of the bottom of the shoe against heat		
CI-insulation of the bottom of the shoe against the cold		
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises	✓	
The shoes do not contain metal parts	✓	
-		
-		
-		

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3213/36	8592390080127	17.75	1.775
G3213/37	8592390080134	18.00	1.800
G3213/38	8592390080141	18.25	1.825
G3213/39	8592390080158	18.50	1.850
G3213/40	8592390080165	18.75	1.875
G3213/41	8592390080172	19.00	1.900
G3213/42	8592390080189	19.25	1.925
G3213/43	8592390080196	19.50	1.950
G3213/44	8592390080202	19.75	1.975
G3213/45	8592390080219	20.00	2.000
G3213/46	8592390080226	20.25	2.025
G3213/47	8592390080233	20.50	2.050
G3213/48	8592390080240	20.75	2.075



ARDON®
WORKWEAR
& OUTDOOR





ARDON®

**WORKWEAR
& OUTDOOR**



TECHNICAL SHEET