



ARDON®
WORKWEAR
& OUTDOOR

ARDON® EBON S2

SAFETY SHOES



DRY AIR



WASH-FRIENDLY



NONMETALLIC

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

ARDON® EBON S2

SAFETY SHOES

ARTICLE G3361

MATERIAL

Upper MICROFIBER with a thickness of 1,4 mm
 Lining MESH laminated breathable fabric
 Sole PU/PU, two-component spray coating, oil resistant, anti-static, antislip composite 459
 Toe cap -
 Plate ANATOMIC GEL – anatomically shaped PU foam with cushioning gel in the heel area
 Insole

SIZE 36-48

UNIT

PACKAGE

Units in a carton 10 pairs
 Units in a box 1 pair

DIMENSIONS

| | 36-41 | 42-48 |
|-----------------------|----------------|-----------------|
| Carton H x W x D (cm) | 59 x 34 x 40,5 | 61,5x 36 x 41,5 |
| Carton (cbm) | 0,0812 | 0,0919 |

| Size EUR | 35 | 36 | 37 | 38 | 39 | 40 | 41 | 42 | 43 | 44 | 45 | 46 | 47 | 48 | 49 | 50 | 51 |
|------------------|----|------|------|------|------|------|------|------|------|------|------|------|------|------|----|----|----|
| Insole length mm | - | 235 | 241 | 248 | 255 | 262 | 270 | 276 | 283 | 290 | 297 | 304 | 310 | 317 | - | - | - |
| Foot length cm | - | 23,0 | 23,6 | 24,3 | 25,0 | 25,7 | 26,5 | 27,1 | 28,3 | 28,5 | 29,2 | 29,9 | 30,5 | 31,2 | - | - | - |

DESCRIPTION

Black safety low shoe is ideal not only for the hospitality industry. The upper is made of microfiber that is washing machine safe up to 30°C. For greater comfort, the shoes were designed with an anatomically shaped insole with a gel component that absorbs shocks during walking and lowers the impact on the heel area. The lightweight dual-density polyurethane outsole meets SRC slip resistance requirements. Safety at work is ensured through the composite toecap.

TECHNICAL SHEET



ARDON[®]
WORKWEAR
 & **OUTDOOR**

NORMS

(EU) 2016/425

EN ISO 20345:2011 Personal protective equipment - Safety footwear

Category S2 SRC

| Categories | EN ISO 20345 | |
|--|--------------|--|
| E - energy absorption in the heel area | ✓ | |
| FO - resistance to oils and fuels | ✓ | |
| A - antistatic footwear | ✓ | |
| SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin | ✓ | |
| WR - upper resistant to water | ✓ | |
| Safety toe cap for toe protection | ✓ | |
| P - resistance to punctures (protective insole) | | |
| SRA - slip resistance ceramic floor tiles with SLS | | |
| HRO - resistance to contact heat up to 300 °C | | |
| HI-insulation of the bottom of the shoe against heat | | |
| CI-insulation of the bottom of the shoe against the cold | | |
| Splatters of molten metal | | |
| ESD – shoe protects against electrostatic discharge and can be used on EPA premises | | |
| The shoes do not contain metal parts | ✓ | |
| - | | |
| - | | |
| - | | |

TECHNICAL SHEET



ARDON®

**WORKWEAR
& OUTDOOR**

| CODE | EAN | CARTON WEIGHT (KG) | UNIT WEIGHT (KG) |
|-------------|---------------|-------------------------------|-----------------------------|
| G3361/36 | 8592390150684 | 10.6 | 1.06 |
| G3361/37 | 8592390150691 | 10.8 | 1.08 |
| G3361/38 | 8592390150707 | 11,0 | 1.10 |
| G3361/39 | 8592390150714 | 11.2 | 1.12 |
| G3361/40 | 8592390150721 | 11.4 | 1.14 |
| G3361/41 | 8592390150738 | 11.6 | 1.16 |
| G3361/42 | 8592390150745 | 11.8 | 1.18 |
| G3361/43 | 8592390150752 | 12,0 | 1.20 |
| G3361/44 | 8592390150769 | 12.2 | 1.22 |
| G3361/45 | 8592390150776 | 12.4 | 1.24 |
| G3361/46 | 8592390150783 | 12.6 | 1.26 |
| G3361/47 | 8592390150790 | 12.8 | 1.28 |
| G3361/48 | 8592390150806 | 13,0 | 1.30 |



ARDON®
WORKWEAR
& OUTDOOR





ARDON®
WORKWEAR
& OUTDOOR



TECHNICAL SHEET