



ARDON[®]
WORKWEAR
& OUTDOOR

ARDON[®] ROVERWIN S3 HRO

SAFETY SHOES



WINTER



FOOT COMFORT



WATER
REPELLENT

TECHNICAL SHEET



ARDON[®]
WORKWEAR
& OUTDOOR

ARDON[®] ROVERWIN S3 HRO

SAFETY SHOES

ARTICLE G3390

MATERIAL

Upper ACTION NUBUK- cowhide leather with polyurethane coating, hydrophobic
 Lining synthetic fur
 Sole PU/rubber, two-component spray coating, oil resistant, anti-static, antislip, resistant up to 300 ° C
 Toe cap composite 431
 Plate kevlar
 Insole ANATOMIC FOAM – anatomically shaped EVA foam, supports longitudinal and transverse arches, absorbs shocks in the heel area

SIZE
UNIT

35-50
 pair

PACKAGE

Units in a carton 10 pairs

Units in a box 1 pair

DIMENSIONS

	35-38	39-43	44-48	49-50
Carton H x W x D (cm)	64,5x 34 x 43,5	64,5x 34 x 51,5	67x38x55,5	69,5x41x57,5
Carton (cbm)	0,0954	0,1129	0,1413	0,1638

Size EUR	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51
Insole length mm	232	239	246	253	259	266	273	280	287	293	300	306	313	319	325	332	-
Foot length cm	22,2	22,9	23,6	24,3	24,9	25,6	26,3	27	27,7	28,3	29	29,6	30,3	30,9	31,5	32,2	-

DESCRIPTION

Safety shoes with an extra wide sole, resistant to contact heat up to 300 ° C and with an upper made of leather with a PU coating. The ANATOMIC FOAM insole ensures increased comfort of the shoes. The shoes are equipped with a composite toe cap and a kevlar insole against punctures.

TECHNICAL SHEET



ARDON[®]
WORKWEAR
 & **OUTDOOR**

NORMS

(EU) 2016/425

EN ISO 20345:2011

Personal protective equipment - Safety footwear

Category

S3 HRO SRC CI HI

Categories	EN ISO 20345	
E - energy absorption in the heel area	✓	
FO - resistance to oils and fuels	✓	
A - antistatic footwear	✓	
SRC - resistance to slipping on ceramic floor tiles with SLS and on steel floors with glycerin	✓	
WRU - upper resistant to water	✓	
Safety toe cap for toe protection	✓	
P - resistance to punctures (protective insole)	✓	
SRA - slip resistance ceramic floor tiles with SLS		
HRO - resistance to contact heatup to 300 °C	✓	
HI-insulation of the bottom of the shoe against heat	✓	
CI-insulation of the bottom of the shoe against the cold	✓	
Splatters of molten metal		
ESD – shoe protects against electrostatic discharge and can be used on EPA premises		
The shoes do not contain metal parts		
-		
-		
-		

TECHNICAL SHEET



ARDON®
WORKWEAR
& OUTDOOR

CODE	EAN	CARTON WEIGHT (KG)	UNIT WEIGHT (KG)
G3390/35	8592390154293	19.2	1.920
G3390/36	8592390154309	19.3	1.925
G3390/37	8592390154316	19.3	1.930
G3390/38	8592390154323	19.4	1.935
G3390/39	8592390154330	19.4	1.940
G3390/40	8592390154347	19.5	1.945
G3390/41	8592390154354	19.6	1.959
G3390/42	8592390154361	19.8	1.975
G3390/43	8592390154378	19.8	1.981
G3390/44	8592390154385	19.8	1.983
G3390/45	8592390154392	19.9	1.988
G3390/46	8592390154408	19.9	1.989
G3390/47	8592390154415	19.9	1.990
G3390/48	8592390154422	20.0	2.000
G3390/49	8592390154439	20.5	2.050
G3390/50	8592390154446	20.9	2.090



ARDON®
WORKWEAR
& OUTDOOR





ARDON®

**WORKWEAR
& OUTDOOR**



TECHNICAL SHEET