



FA 20 300 02, FA 20 301 02

VORAS



| |
|---|
| HS CODE |
| 84798997 |
| CARTON SIZE / PCS. |
| 60 x 40 x 24 cm / 10 |
| AET N°2777/10835-01/E12-02 |
| Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland |
| MODULE D FI14/14003.02 |
| SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland |

| REF. | FA 20 300 02 | FA 20 301 02 |
|---------------|------------------------|--------------------|
| LG. KG | 2.50 m | |
| | EN 360:2002 | |
| MAT. | PVC | |
| | PA & PES 50 mm | |
| | --- / FA 50 101 17 | --- / FA 50 202 17 |
| | x1 | |
| R(kN) | 15 kN | |
| | NO | |
| | 1.15 KG | 1.20 KG |

LG.

 KG

Longueur Poids maxi utilisateur
Length Max. user weight
Longitud Peso máximo del usuario
Lunghezza Peso Max. dell'utente
Länge Höchstgewicht des Benutzers

MAT.

Matière carter / sangle
 Material of casing / webbing
Material cárter / correa
 Material dei carter / Cinghia
Material Gehäuse / Gurt

Matière connecteur haut / connecteur bas
 Material of top connector / bottom connector
Material conector alto / conector bajo
 Materiale connettore alto / connettore basso
Material oberes / unteres Verbindungselement

Nombre d'émerillons
 Number of swivels
Cantidad de eslabones giratorios
 Numero di tornichetti
Anzahl der Wirbel

Homologué pour le travail à proximité d'arêtes vives
 Approved for work near sharp edges
Homologado para trabajo cerca de aristas vivas
 Omologato per lavoro in prossimità di spigoli vivi
Zugelassen für Arbeiten in der Nähe scharfer Kanten