






| |
|---|
| HS CODE |
| 6307909899 |
| CARTON SIZE / PCS. |
| 60 x 40 x 24 cm / 5 |
| AET (UE) N°2777/13781-01/E01-01 |
| Satra Technology Europe Ltd., N° 2777, Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland |
| MODULE D FI14/14003.02 |
| SGS Fimko Oy, N°0598 Takomotie 8, 00380 HELSINKI, Finland |

| | |
|--|--|
| REF. | FA 60 007 00 |
| CE | PPE regulation (EU) 2016/425 Annex II using EN 795:2012, TS 16415:2013 |
|  | x2 |
| MAT. |  30 mm PES |
| R (kN) / MBS (kN) | 19 kN / 23 kN |
| MAT.  |  |
| LG. / f MIN. → MAX. | 5.0 m → 20.0 m / 0.8 m → 3.2 m |
|  | 3.43 KG |



R (kN) / MBS (kN)

Nombre d'utilisateurs
Number of users
Cantidad de usuarios
Cantidad di utilizzatori
Anzahl der Benutzer

Résistance statique (en kN) / Résistance à la rupture
Static strength / Minimum Breaking Strength
Resistencia estática (en kN) / Resistencia a la ruptura (en kN)
Resistenza statica (in kN) / Resistenza alla rottura (in kN)
Statische Festigkeit (in kN) / Bruchfestigkeit (in kN)



LG. / f MIN. MAX.

Matière connecteur / tendeur
Material of connector / tensioner
Material del conector / tensor
Materia del connetore / tenditore
Material Verbinder / Spanner

Longueur mini → maxi / Flèche mini → maxi
Min. → Max. length / Min. → Max. deflection
Longitud mínima → máxima / Flecha mínima → máxima
Lunghezza min. → max. / Flessione min. → max.
Länge min. → max. / Dirchhang min. → max.