


FA 60 0006 10/20:

PVC +  **STEEL**

FA 60 006 10S/20S:

PVC +  **INOX****HS CODE**

76169990





**CARTON SIZE / PCS.****FA 60 006 10/S : 40 x 40 x 24 cm / 25****FA 60 006 20/S : 40 x 40 x 24 cm / 20**

FA 60 006 XX: AET (UE) N°2777/11681-01/E00-00

FA 60 006 XXS: AET (UE) N°2777/10792-02/E01-01

**Satra Technology Europe Ltd., N° 2777,**  
 Bracetown Business Park, Clonee,  
 Dublin, D15YN2P, Ireland

**MODULE D FI14/14003.02****SGS Fimko Oy, N°0598**
 Takomotie 8,  
 00380 HELSINKI, Finland

|   |  |
|---|--|
| REF.  | FA 60 006 10   FA 60 006 20   FA 60 006 10S   FA 60 006 20S  |
| CE  | EN 795:2012 Type B   |
|    | x1   |
| LG.   | 1.0 m   2.0 m   1.0 m   2.0 m  |
| MAT.  | PVC /  STEEL Ø 8.0 mm   PVC /  INOX Ø 8.0 mm |
| R (kN) / MBS (kN)   | 12 kN / 25 kN  |
|  | 0.56 kg   0.80 kg   0.46 kg   0.74 kg  |



**Nombre d'utilisateurs**  
 Number of users  
**Cantidad de usuarios**  
 Quantità di utilizzatori  
**Anzahl der Benutzer**

**R (kN) / MBS (kN)**

**Résistance statique (en kN) / Résistance à la rupture**  
 Static strength / Minimum Breaking Strength  
**Resistencia estática (en kN) / Resistencia a la ruptura (en kN)**  
 Resistenza statica (in kN) / Resistenza alla rottura (in kN)  
**Statische Festigkeit (in kN) / Bruchfestigkeit (in kN)**